

SI-200 Specifications

Bandwidth	DC to 200MHz (-3dB)
Attenuation Ratio	1:10
Accuracy	±1%
Rise Time	1.75ns
Input Impedance	500kΩ//7pF each side ground
Input Voltage	
- Differential Range	±20V (DC + AC Peak) and 20Vrms
- Common Mode Range	±60V (DC + AC Peak) and 60Vrms
- Absolute Max. Voltage (either input to ground)	±60V (DC + AC Peak) and 60Vrms
Output	
- Swing	±2V (into 50Ω load)
- Offset (typical)	<±2mV
- Noise (typical)	0.3mVrms
- Source Impedance (typical)	50Ω (for using 50Ω input system oscilloscope)
CMRR (typical)	- 80 dB @ 60Hz, -50dB @10MHz
Power Requirements**	
- Standard	One 9V battery
- Options	Power leads, Mains adaptor** (6VDC/500mA or 9VDC/300mA)
Ambient Operating Temperature	-10 to 40°C
Ambient Storage Temperature	-30 to 70°C
Ambient Operating Humidity	Up to 85% RH
Ambient Storage Humidity	Up to 85% RH
Length of BNC Cable	120cm
Length of Input Leads	50cm
Weight	200gms
Dimensions (LxWxH)	111mm x 22mm x 14mm

- **
- For wrong polarity of power sources, a built-in circuit will protect the probe and no danger or damage will occur.
 - When the voltage of the cells become too low, the power indicator on the panel will flicker.